Declaration of performance according to Regulation (EU) 305/2011

No. Ci30-CPR-130912-SE-2



PRODUCT

Insert lit with solid biofuels Product type

Type designation Contura i30

Manufacturing number See rating plate on the insert

Intended area of use Heating of rooms in residential buildings

MANUFACTURER

NIBE AB / Contura Name Address Box 134, Skulptörvägen 10 SE-285 23 Markaryd, Sweden

CHECKS

According to AVCP System 3

EN 13229:2001/AC:2006, EN-13229:2001/A2:2004/AC:2007 European standard

Test institute Rein-Ruhr Feuerstätten Prüfstelle, NB 1625,

has checked declared performance and issued test report no. RRF-29 13 3371

DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	NPD	
Minimum distance to combustible material	Rear: 150 mm Side: 150 mm Follow the given conditions in the installation instructions.	
Risk of falling embers	Pass	EN 13229:2001/AC:2006, EN-13229:2001/A2:2004/AC:2007
Emissions from combustion	CO 0,07%	
Surface temperatures	Pass	
Cleaning options	Pass	
Mechanical durability	Pass	
Emissions of hazardous substances	Pass	
Nominal output	6,0 kW	
Efficiency	81%	
Flue gas temperature in connector at nominal output	283°C	

The undersigned is responsible for the manufacture and conformity with the declared performance.

Niklas Gunnarsson, Business area manager NIBE STOVES

Markaryd, September 12, 2013